


















Product quality		
Formats		914 x 457 x 6,0 mm
Packaging	Pack:	5 elements / 2.088 m ² / 21.067 kg
	Pallet:	40 packs / 83,540 m ² / 882,66 kg

Tolerances (Requirement EN 16511:2014)		
Squareness of the elements ($\leq 0.20\text{mm}$)		$\leq 0,15\text{ mm}$
Determination of Linearity ($\leq 0.30\text{ mm/m}$)		$\leq 0,20\text{ mm/m}$
Flatness concave / convex	lengthwise ($\leq 0.50/\leq 1.0\%$)	$\leq 0,30/\leq 0,50\%$
	wide ($\leq 0.15/\leq 0.20\%$)	$\leq 0,10/\leq 0,15\%$
Surface flushness	(average $\leq 0.10\text{ mm}$)	(average $\leq 0.10\text{ mm}$)
	(max. $\leq 0.15\text{ mm}$)	(max. $\leq 0.15\text{ mm}$)
Opening between installed elements	(average $\leq 0.15\text{ mm}$)	(average $\leq 0,05\text{ mm}$)
	(max. $\leq 0.20\text{ mm}$)	(max. $\leq 0.10\text{ mm}$)

Guarantee (according Parador guarantee conditions)		Notes
Domestic area	Commercial area	- suitable for all-over adhesion (see notes in our advisor)
Lifetime	10 years	- cleaning an maintenance see instructions
		- technical changes reserved

Classification			
		Test method	Rating
	Utility class 23 domestic areas with intensive use	EN 16511	Living room, hall, kitchen, home office
	Utility class 33 commercial areas with intensive use	EN 16511	Classrooms, open-plan offices, shops
	Reaction to fire	EN 13501-1	B _f -s1
	Slip resistance	EN 13893 EN 14041	$\mu \geq 0,30$ DS
	Staining resistance	EN 438-2	Category 1 + 2: level 5, no visible change Category 3: level 4, slight change
	Light fastness	EN ISO 105 - B02	Blue wool scale: Stage ≥ 6
	Resistance to roller castor chairs	EN 425	Type W, no visible changes
	Moving a furniture leg	EN 424	No visible changes
	Indentation-residual	EN ISO 24343-1	$\leq 0,10\text{ mm}$
	Formaldehyde emission (E1 = 0.1 ppm)	ISO 16000	< E1
	Acoustical - Impact noise reduction	EN ISO 10140	17 dB
	Length- and Square separating force	ISO 24334	lengthwise $\geq 4\text{ KN/m}$ transversely $\geq 3\text{ KN/m}$
	Abrasion	prEN 15468 Annex A	> 5.000 rev.
	Dimensional stability	EN ISO 23999	$\leq 0,20\%$
	Micro scratch resistance	EN 16094	Method A MSR-A1
	Antimicrobial activity	ISO 22196	Antibacterial
	Slip resistance on an inclined plane	ISO 22196	Mineral texture: R9
	Disposal	EAK-Code-number	20 01 39
	Suitable for damp rooms: 100% waterproof product construction enables use in damp rooms (please observe installation instructions).		

Changed:	QMB Parador	File:	PA_TDS_Designboden_Vinyl_Trendime-5_EN_20210501
Date:	15.12.2018	Latest update at:	https://parador.de/en/partner/downloads/index/cat/11/
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.05.2021