





















Product quality						
Formats		Basic 200 (Utility class 23 + 31)	Basic 200 V (Utility class 23 + 31)	Basic 400 / 400 V (Utility class 23 + 32)	Basic 600 V (Utility class 23 + 32)	
		1285 x 194 x 7 mm	1285 x 194 x 7 mm	1285 x 194 x 8 mm	1285 x 243 x 8 mm	2200 x 243 x 8 mm
Packaging	Pack:	12 Elements	11 Elements	10 Elements	7 Elements	6 Elements
		2.992 m <sup>2</sup> / 19.44 Kg	2.742 m <sup>2</sup> / 18.7 Kg	2.493 m <sup>2</sup> / 17.40 Kg	2.186 m <sup>2</sup> / 15.8 Kg	3.208 m <sup>2</sup> / 23.19 Kg
	Pallet:	40 Pack	40 Pack	40 Pack	42 Pack	39 Pack
		119.66 m <sup>2</sup> / 792.6 Kg	109.69 m <sup>2</sup> / 763 Kg	99.716 m <sup>2</sup> / 711 Kg	91.80 m <sup>2</sup> / 679.7 Kg	125.1 m <sup>2</sup> / 920.4 Kg
Guarantee		Domestic area: 12 Years (According Parador guarantee conditions)			Notes	- not ready for glue-down
		Commercial area: -				- cleaning an maintenance see intruction
						- technical changes reserved

Product labeling						Tolerances (EN 13329)		
							Squarerness of elements (≤ 0,20 mm)	≤ 0.10 mm
						Determining the straightness of the edges (≤ 0,30 mm/m)		≤ 0.10 mm/m
						Height differences of the elements		(average ≤ 0.10 mm) mittel ≤ 0.05 mm (max. ≤ 0.15 mm) max. ≤ 0.10 mm
						Opening between installet elements		(average ≤ 0.15 mm) mittel ≤ 0.05 mm (max. ≤ 0.20 mm) max. ≤ 0.10 mm
						Block alignment		± 2 mm

Classification product features							
		Test standard	Rating			Test standard	Rating
	<b>Utility class 23</b> domestic areas with intensive use	EN 13329	Living room, hall, kitchen, home office		Slip resistance	EN 13893 EN 14041	μ ≥ 0.35 DS
	<b>Utility class 31</b> commercial areas with medium use	EN 13329	Hotels, small offices		Electrical behaviour	EN 1815	-
	<b>Utility class 32</b> commercial areas with medium use	EN 13329	Classrooms, small offices, shops		<b>Thermal conductivity</b> Underfloor heating – suitable, with the backing material and vapor barrier	EN 12664	0.043 m <sup>2</sup> *K/W
	Abrasion	EN 13329, Annex E	Basic 200: AC 3 (≥ 2.000 rpm.) Basic 400/600: AC 4 (≥ 4.000 rpm.)		Resistance to roller castor chairs	EN 425	No visible changes
	Impact resistance	EN 13329, Annex F	Basic 200: IC 1 Basic 400-600: IC 2		Effect of a furniture leg	EN 424	No visible changes
	Reaction to fire	EN 13501-1	C <sub>fl</sub> s1		Indentation-residual	EN 433	No visible changes
	Staining resistance	EN 438-2	Category 1 + 2: level 5 Category 3: level 4/5		Locking strength of mechanically assembled panels	ISO 24334	-
	Cigarette resistance	EN 438-2	level 4		Accoustical impact noise reduction	ISO 717-2	14 db (with Akustik-Protect 100)
	Light fastness	EN ISO 105 – B02 EN 20105 – A02	Blue wool scale: Stage ≥ 6 Grey scale: Stage ≥ 4		Dimensional stability	ISO 24339	-
	Formaldehyde (E1 = 0.1 ppm)	EN 717-1	≤ 0.05 ppm		Surface soundness	EN 433	Basic 200: ≥ 1,6 N/mm <sup>2</sup> Basic 200 V/400/600: ≥ 1,8 N/mm <sup>2</sup>
	Thickness swelling	EN 13329, Annex G (≤ 18 %)	Basic 200: ≤ 15 % Basic 200 V/400/600: ≤ 13 %		Slip resistance on an inclined plane	DIN 51130	Depending on structure: -/R 9/R 10
	Scratch resistance	EN 438	Level 4		Disposal	Privat waste disposal with normal household waste, bulky waste possible	

Changed:	QMB	File:	PA_TDS_Laminat_Basic_EN_2015
Date:	01.01.2014	Updates at:	<a href="http://www.parador.de">www.parador.de</a>
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:		01.05.2015	